

GOLDSEAL GROUP

Rust Proof Services NZ (2005) Ltd
40 Northway Street,
Hamilton, New Zealand.
P O Box 20466, Te Rapa.
Telephone: 07 849 9253
Mobile: 0276 315 657
rustproofservices@goldseal.co.nz



SPECIFICATIONS

INDUSTRIAL SPRAY GRADE COMPOUND

- Description:** A special blend of petroleum waxes, process oils, sterates, wetting agents, inhibitors and chemicals designed to combat rust and halt further corrosion on a large variety of steel work. It will not chip, crack or harden, and because of its very flexible nature, readily penetrates into crevices, welds, and bolted joints. MAF APPROVED
- Preparation:** All scale rust and grime should be removed by chipping and/or wire brushing to leave a clean dry surface prior to application. If surfaces are exposed to salt water spray they should be washed with fresh water to remove contamination. Sandblasting is not a prerequisite of Industrial Spray Grade Compound.
- Application:** By airless spray equipment after being heated in excess of 70 degrees Celsius to achieve maximum effectiveness and penetration. Not for use where human traffic has access.
- Coverage:** 2.0m² per litre will give a final coating of 300 microns. One coat only being required.
- Thinning:** Not recommended.
- Solvent:** Stoddards Solvent (Cleaning purposes only)
- Colours:** Dark Red, Brown or Charcoal.
- Availability:** Only through Licensed Applicators.